

2026 MULTI SPLIT OUTDOOR UNITS - R32

Multi Split Outdoor Units - R32 - Single Phase 2 Way Multi Outdoors



Outdoor Unit		AOEG14KBCA2	AOEG18KBCA2
Maximum Connectable Indoor Units		2	2
Nominal Cooling Capacity (Range)	kW	4.0 (1.4-4.6)	5.0 (1.7-5.8)
Nominal Heating Capacity (Range)	kW	4.4 (1.1-5.5)	5.6 (1.8-6.6)
EER Cooling / COP Heating		4.12 / 4.63	4.03 / 4.59
Dimensions (H x W x D)	mm	542x799x290	632x799x290
Weight	kg	33	37
Sound Pressure Level Cooling / Heating	dB(A)	47 / 49	47 / 50
Max Pipe Length Total / Each	m	30 / 20	30 / 20
Max height Difference - Between OU & Each IUt	m	15	15
Max height Difference - Between Indoor Units	m	10	10
Refrigerant Type (Global Warming Potential)		R32 (675)	R32 (675)
Refrigerant Charge kg / CO2eq-T		0.9 (0.608)	1.02 (0.689)
Operation Range Cooling		-10°C to 46°C	-10°C to 46°C
Operation Range Heating		-15°C to 24°C	-15°C to 24°C
Power Source / Suggested Fuse Size		1Ph-230V-50Hz	1Ph-230V-50Hz
Outdoor Price		£1,165	£1,401

3 Way Multi Outdoors



Outdoor Unit		AOEG18KBCA3	AOEG24KBCA3
Maximum Connectable Indoor Units		3	3
Nominal Cooling Capacity (Range)	kW	5.4 (1.8-7.0)	6.8 (1.8-8.5)
Nominal Heating Capacity (Range)	kW	6.8 (2.0-8.0)	8.0 (2.0-9.2)
EER Cooling / COP Heating		4.78 / 4.89	3.90 / 4.40
Dimensions (H x W x D)	mm	716x820x315	716x820x315
Weight	kg	46	46
Sound Pressure Level Cooling / Heating	dB(A)	46 / 49	48 / 53
Max Pipe Length Total / Each	m	50 / 25	50 / 25
Max height Difference - Between OU & Each IUt	m	15	15
Max height Difference - Between Indoor Units	m	10	10
Refrigerant Type (Global Warming Potential)		R32 (675)	R32 (675)
Refrigerant Charge kg / CO2eq-T		1.80 (1,215)	1.80 (1,215)
Operation Range Cooling		-10°C to 46°C	-10°C to 46°C
Operation Range Heating		-15°C to 24°C	-15°C to 24°C
Power Source / Suggested Fuse Size		1Ph-230V-50Hz	1Ph-230V-50Hz
Outdoor Price		£1,903	£1,979

4 & 5 Way Multi Outdoors



Outdoor Unit		AOEG30KBT4	AOEG36KBT45
Maximum Connectable Indoor Units		4	5
Nominal Cooling Capacity (Range)	kW	8.0 (2.4-10.1)	9.5 (3.0-11.0)
Nominal Heating Capacity (Range)	kW	9.6 (3.0-11.2)	10.6 (3.5-12.0)
EER Cooling / COP Heating		3.90 / 4.55	3.80 / 4.50
Dimensions (H x W x D)	m	844x820x315	844x820x315
Weight	kg	55	59
Sound Pressure Level Cooling / Heating	dB(A)	50 / 54	52 / 55
Max Pipe Length Total / Each	mm	70 / 25	75 / 25
Max height Difference - Between OU & Each IUt	m	15	15
Max height Difference - Between Indoor Units	m	10	10
Refrigerant Type (Global Warming Potential)		R32 (675)	R32 (675)
Refrigerant Charge kg / CO2eq-T		2.20 (1,485)	2.50 (1,688)
Operation Range Cooling		-10°C to 46°C	-10°C to 46°C
Operation Range Heating		-15°C to 24°C	-15°C to 24°C
Power Source / Suggested Fuse Size		1Ph-230V-50Hz	1Ph-230V-50Hz
Outdoor Price		£2,694	£3,476

2026 MULTI SPLIT INDOOR UNITS - R32

Multi Split Indoor Units

Please consult with the technical manuals for allowable system combinations
With built in Wi-Fi



Wall mounted type - KNCA Indoors

Model		Indoor unit		ASEH05KNCA		ASEH07KNCA		ASEH09KNCA		ASEH12KNCA			
kW Class			kW		1.5		2.0		2.5		3.5		
Power Source													
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	34 / 33 / 29 / 21		36 / 33 / 29 / 21		41 / 35 / 29 / 21		42 / 36 / 32 / 21			
	Heating			34 / 32 / 30 / 22		36 / 33 / 30 / 22		41 / 34 / 30 / 22		42 / 35 / 31 / 22			
Sound Power Level	Cooling	H	dB(A)	50		51		56		57			
	Heating			50		51		56		57			
Airflow Rate	Cooling	H/M/L/Q	m³/h	500 / 450 / 390 / 250		530 / 460 / 390 / 250		640 / 500 / 390 / 250		660 / 520 / 440 / 250			
	Heating			500 / 450 / 420 / 280		530 / 460 / 420 / 280		640 / 500 / 420 / 280		660 / 520 / 440 / 280			
Net Dimensions			mm		270 x 784 x 222		270 × 784 × 222		270 × 784 × 222		270 × 784 × 222		
Weight			kg (lbs)		9		9 (19)		9 (19)		9 (19)		
Connection Pipe Diameter		Liquid / Gas		mm		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")	
Indoor Price				£261		£289		£307		£344			



Wall mounted type - KM Indoors

Model	Indoor unit			ASEH07KMCG	ASEH09KMCG	ASEH12KMCG	ASEH14KMCG
kW Class			kW	2.0	2.5	3.5	4.0
Power Source				Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38 / 33 / 29 / 21	40 / 34 / 29 / 21	40 / 35 / 30 / 21	43 / 36 / 30 / 21
	Heating			41 / 35 / 31 / 22	42 / 36 / 31 / 22	42 / 38 / 33 / 22	44 / 39 / 33 / 24
Sound Power Level	Cooling	H	dB(A)	54	55	55	57
	Heating			56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	650 / 540 / 430 / 320	700 / 560 / 430 / 320	700 / 560 / 430 / 320	770 / 600 / 450 / 310
	Heating			720 / 580 / 460 / 330	750 / 610 / 470 / 330	780 / 640 / 520 / 330	820 / 660 / 520 / 340
Net Dimensions			mm	270 × 834 × 222	270 × 834 × 222	270 × 834 × 222	270 × 834 × 222
Weight			kg (lbs)	10 (22)	10 (22)	10 (22)	10 (22)
Connection Pipe Diameter		Liquid / Gas	mm	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")
Indoor Price				£337	£381	£405	£482



Wall mounted type - KM Indoors - Soft Black

Model	Indoor unit			ASEH07KMCG-B	ASEH09KMCG-B	ASEH12KMCG-B	ASEH14KMCG-B
kW Class			kW	2.0	2.5	3.5	4.0
Power Source				Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38 / 33 / 29 / 21	40 / 34 / 29 / 21	40 / 35 / 30 / 21	43 / 36 / 30 / 21
	Heating			41 / 35 / 31 / 22	42 / 36 / 31 / 22	42 / 38 / 33 / 22	44 / 39 / 33 / 24
Sound Power Level	Cooling	H	dB(A)	54	55	55	57
	Heating			56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	650 / 540 / 430 / 320	700 / 560 / 430 / 320	700 / 560 / 430 / 320	770 / 600 / 450 / 310
	Heating			720 / 580 / 460 / 330	750 / 610 / 470 / 330	780 / 640 / 520 / 330	820 / 660 / 520 / 340
Net Dimensions			mm	270 × 834 × 222	270 × 834 × 222	270 × 834 × 222	270 × 834 × 222
Weight			kg (lbs)	10 (22)	10 (22)	10 (22)	10 (22)
Connection Pipe Diameter		Liquid / Gas	mm	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")
Indoor Price				£401	£446	£470	£551



Wall mounted type - KM Indoors

Model	Indoor unit			ASEH18KMTGL	ASYG22KMTB	ASEH24KMTGL
kW Class			kW	5.0	6.0	7.0
Power Source				Single phase, ~230 V, 50 Hz		
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	45 / 40 / 35 / 29	48 / 40 / 35 / 29	49 / 40 / 35 / 29
	Heating			46 / 40 / 35 / 29	48 / 40 / 35 / 29	49 / 40 / 35 / 29
Sound Power Level	Cooling	H	dB(A)	60	62	65
	Heating			61	62	65
Airflow Rate	Cooling	H/M/L/Q	m³/h	980 / 810 / 640 / 510	1,060 / 810 / 640 / 510	1,170 / 850 / 640 / 510
	Heating			1,020 / 850 / 640 / 510	1,060 / 850 / 640 / 510	1,170 / 850 / 640 / 510
Net Dimensions			mm	280 × 980 × 240	280 × 980 × 240	280 × 980 × 240
Weight			kg (lbs)	12.5 (27)	12.5 (27)	12.5 (27)
Connection Pipe Diameter		Liquid / Gas	mm	6.35 (1/4") / 12.70 (1/2")	6.35 (1/4") / 12.70 (1/2")	6.35 (1/4") / 12.70 (1/2")
Indoor Price				£649	£803	£942

2026 MULTI INDOOR UNITS - R32

Multi Split Indoor Units

Please consult with the technical manuals for allowable system combinations

Floor



Model		Indoor unit		AGEG09KVCA		AGEG12KVCA		AGEG14KVCA	
kW Class			kW	2.5		3.5		4.0	
Power Source				Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	39 / 34 / 28 / 22		42 / 36 / 30 / 22		44 / 38 / 31 / 22	
	Heating			39 / 35 / 30 / 22		42 / 38 / 32 / 22		44 / 39 / 33 / 22	
Sound Power Level	Cooling	H	dB(A)	52		55		56	
	Heating			52		55		56	
Airflow Rate	Cooling	H/M/L/Q	m³/h	530 / 440 / 360 / 270		600 / 490 / 380 / 270		650 / 520 / 400 / 270	
	Heating			530 / 460 / 380 / 270		600 / 510 / 410 / 270		650 / 540 / 430 / 270	
Net Dimensions			mm	600 × 740 × 200		600 × 740 × 200		600 × 740 × 200	
Weight			kg (lbs)	14 (31)		14 (31)		14 (31)	
Connection Pipe Diameter		Liquid / Gas	mm	6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")	
Indoor Price				£729		£844		£983	

Ceiling



Model		Indoor unit		ABEG18KRTA		ABEG22KRTA	
kW Class			kW	5.0		6.0	
Power Source				Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38 / 36 / 33 / 31		42 / 37 / 34 / 31	
	Heating			38 / 36 / 33 / 31		42 / 37 / 34 / 31	
Sound Power Level	Cooling	H	dB(A)	53		57	
	Heating			53		57	
Airflow Rate	Cooling	H/M/L/Q	m³/h	840 / 790 / 710 / 650		900 / 790 / 710 / 650	
	Heating			840 / 790 / 710 / 650		900 / 790 / 710 / 650	
Net Dimensions			mm	235 × 1,080 × 705		235 × 1,080 × 705	
Weight			kg (lbs)	24(52)		24(52)	
Connection Pipe Diameter		Liquid / Gas	mm	6.35 (1/4") / 12.70 (1/2")		6.35 (1/4") / 12.70 (1/2")	
Indoor Price				£702		£908	

Compact Cassette Grid Type



Model			Indoor unit		AUXG07KVLA		AUXG09KVLA		AUXG12KVLA		AUXG14KVLA		AUXG18KVLA		AUXG22KVLA		
kW Class				kW		2.0		2.5		3.5		4.0		5.0		6.0	
Power Source						Single phase, ~230 V, 50 Hz											
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	33 / 31 / 29 / 27		33 / 31 / 29 / 27		37 / 34 / 31 / 28		38 / 35 / 32 / 29		38 / 35 / 32 / 29		44 / 42 / 36 / 30			
	Heating			34 / 32 / 29 / 27		34 / 32 / 29 / 27		37 / 34 / 31 / 29		43 / 38 / 34 / 30		43 / 38 / 34 / 30		45 / 43 / 40 / 33			
Sound Power Level	Cooling	H	dB(A)	46		46		49		50		50		56			
	Heating			47		47		49		55		55		57			
Airflow Rate	Cooling	H/M/L/Q	m³/h	540 / 490 / 440 / 390		540 / 490 / 440 / 390		610 / 530 / 470 / 410		680 / 580 / 490 / 410		680 / 580 / 490 / 410		830 / 740 / 600 / 450			
	Heating			540 / 490 / 440 / 390		540 / 490 / 440 / 390		610 / 530 / 470 / 410		790 / 680 / 580 / 450		790 / 680 / 580 / 450		860 / 760 / 700 / 530			
Net Dimensions				mm		245 × 570 × 570		245 × 570 × 570		245 × 570 × 570		245 × 570 × 570		245 × 570 × 570			
Weight				kg (lbs)		15 (33)		15 (33)		15 (33)		15 (33)		16 (35)			
Panel						UTGUFYFW		UTGUFYFW		UTGUFYFW		UTGUFYFW		UTGUFYFW			
Connection Pipe Diameter				Liquid / Gas		mm		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 12.70 (1/2")		6.35 (1/4") / 12.70 (1/2")	
Indoor Price				£524		£548		£584		£637		£713		£732			

Price excludes grille, Grille (UTG-UFYFW) List Price £173

Mini duct



Model		Indoor unit		ARXG07KSLAP		ARXG09KSLAP		ARXG12KSLAP		ARXG14KSLAP		ARXG18KSLAP			
kW Class			kW		2.0		2.5		3.5		4.0		5.0		
Power Source				Single phase, ~230 V, 50 Hz											
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	29 / 26 / 24 / 23		29 / 26 / 24 / 23		31 / 27 / 25 / 23		35 / 30 / 27 / 23		33 / 29 / 26 / 23			
	Heating			29 / 26 / 24 / 23		29 / 26 / 24 / 23		31 / 27 / 25 / 23		35 / 30 / 27 / 23		33 / 29 / 26 / 23			
Sound Power Level	Cooling	H	dB(A)	52		54		55		60		58			
	Heating			53		56		57		62		59			
Airflow Rate	Cooling	H/M/L/Q	m³/h	550 / 440 / 390 / 360		600 / 450 / 400 / 360		650 / 490 / 430 / 360		800 / 640 / 530 / 360		940 / 750 / 540 / 480			
	Heating			550 / 440 / 390 / 360		600 / 450 / 400 / 360		650 / 490 / 430 / 360		800 / 640 / 530 / 360		940 / 750 / 540 / 480			
Net Dimensions			mm		198 × 700 × 450		198 × 700 × 450		198 × 700 × 450		198 × 700 × 450		198 × 900 × 450		
Weight			kg (lbs)		15.5 (34)		15.5 (34)		15.5 (34)		15.5 (34)		18.5 (40)		
Connection Pipe Diameter		Liquid / Gas	mm		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 9.52 (3/8")		6.35 (1/4") / 12.70 (1/2")		
External static pressure			Pa		0 to 30		0 to 30		0 to 30		0 to 50		0 to 50		
Drain pump						Standard		Standard		Standard		Standard		Standard	
Indoor Price				£786		£802		£975		£1,075		£1,076			

2026 MULTI SPLIT INDOOR UNITS- R32

Multi Split Indoor Units

Please consult with the technical manuals for allowable system combinations



Slim duct

Indoor unit				ARXG07KLLAP	ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP
kW Class		kW		2.0	2.5	3.5	4.0	5.0
Power Source				Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	28 / 26 / 25 / 24	28 / 27 / 26 / 25	29 / 28 / 27 / 26	32 / 30 / 28 / 26	32 / 30 / 29 / 27
	Heating			28 / 26 / 25 / 24	28 / 26 / 25 / 24	29 / 28 / 27 / 24	32 / 30 / 28 / 25	32 / 30 / 29 / 27
Sound Power Level	Cooling	H	dB(A)	57	57	58	60	58
	Heating			57	57	58	60	58
Airflow Rate	Cooling	H/M/L/Q	m³/h	550 / 490 / 470 / 440	600 / 550 / 500 / 450	650 / 600 / 550 / 480	800 / 700 / 600 / 480	940 / 880 / 820 / 750
	Heating			550 / 490 / 470 / 440	600 / 550 / 500 / 450	650 / 600 / 550 / 480	800 / 700 / 600 / 480	940 / 880 / 820 / 750
Net Dimensions			mm	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 900 × 620
Weight			kg (lbs)	16 (35)	17 (37)	17 (37)	17 (37)	20 (44)
Connection Pipe Diameter		Liquid / Gas	mm	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 9.52 (3/8")	6.35 (1/4") / 12.70 (1/2")
External static pressure			Pa	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90
Drain pump				Standard	Standard	Standard	Standard	Standard
Indoor Price				£668	£655	£729	£870	£951



Medium Static Pressure Duct

Model				Indoor unit		ARXG22KMLB	
kW Class				kW		6.0	
Power Source				Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	31 / 29 / 27 / 25			
	Heating			31 / 29 / 27 / 25			
Sound Power Level	Cooling	H	dB(A)	60			
	Heating			62			
Airflow Rate	Cooling	H/M/L/Q	m³/h	1,100 / 910 / 750 / 580			
	Heating			1,100 / 910 / 750 / 580			
Net Dimensions			mm	270 × 1,135 × 700			
Weight			kg (lbs)	35 (77)			
Connection Pipe Diameter		Liquid / Gas	mm	6.35 (1/4") / 12.70 (1/2")			
External static pressure			Pa	30 to 150			
Drain pump			Standard				
Indoor Price			£924				

Price excludes filter & Spigot - list price £ £84 / £42

Multi Outdoor Combinations and Capacity

Outdoor Unit	Min/Max I/Ds	Min/Max Connectable Capacity (BTU)	Max Pipe length Total/Each	Pipe Sizes	
				Gas	Liquid
AOEG14KBTA2	2 / 2	14,000 - 21,000	30 / 20	3/8 x 2	1/4 x 2
AOEG18KBTA2	2 / 2	14,000 - 26,000	30 / 20	3/8 x 2	1/4 x 2
AOEG18KBTA3	2 / 3	14,000 - 30,000	50 / 25	3/8 x 3	1/4 x 3
AOEG24KBTA3	2 / 3	14,000 - 36,000	50 / 25	3/8 x 2 + 1/2 x 1	1/4 x 3
AOEG30KBTA4	2 / 4	25,000 - 49,000	70 / 25	3/8 x 2 + 1/2 x 2	1/4 x 4
AOEG36KBTA5	2 / 5	27,000 - 54,000	75 / 25	3/8 x 3 + 1/2 x 2	1/4 x 5