



# Wall mounted Active

## FAA-B / AZAS-M/R *SkyAir Active-series*

**R-32** BLUEEVOLUTION

Conveniently surface mounted  
Also for rooms with no false ceilings

- › Combinations with Sky Air Active series ensures good value for money for all types of commercial applications
- › Flat, stylish front panel blends easily within any interior and is easier to clean
- › Can easily be installed in both new and refurbishment projects
- › Reduced energy consumption thanks to specially developed DC fan motor
- › The air is comfortably directed up and down to suit your needs, thanks to 5 different discharge angles that can be programmed via the remote control
- › Maintenance operations can be performed easily from the front of the unit



FAA-B



ARXM71R

AZAS100M



Madoka BRC1H52W

**WI-FI CONTROL VIA APP**

**WI-FI ADAPTOR AVAILABLE AS AN OPTION**

BRC7EA631/2 (optional)



# FAA-B / AZAS-M/R

SkyAir Active-series

R-32

BLUEEVOLUTION

Indoor Units			Single Phase		3 Phase
			FAA71B	FAA100B	FAA100B
Capacity	UK Total Cooling	kW	6.65	10.80	10.80
	UK Sensible Cooling	kW	4.15	7.44	7.44
	Nominal Cooling	kW	6.8	9.5	9.5
	Nominal Heating	kW	7.5	10.8	10.8
Seasonal Efficiency (EN14825) COOLING	Energy Label		A+	A	A
	Pdesign	kW	6.8	9.5	9.5
	SEER		5.77	5.25	5.25
	Annual Energy Consumption	kWh	412	633	633
Seasonal Efficiency (EN14825) HEATING	Energy Label		A	A	A
	Pdesign	kW	4.5	6.0	6.0
	SCOP		3.81	3.81	3.81
	Annual Energy Consumption	kWh	1652	2205	2205
Air Flow Rate (Cooling)	High / Med / Low	m³/sec	0.270 / 0.223 / 0.202	0.433 / 0.383 / 0.317	0.433 / 0.383 / 0.317
Dimensions	Height	mm	290	340	340
	Width	mm	1050	1200	1200
	Depth	mm	269	262	262
Weight		kg	14	18	18
Sound Pressure (Cooling)	High / Med / Low	dBA	45 / 42 / 40	49 / 45 / 41	49 / 45 / 41
Sound Pressure (Heating)	High / Med / Low	dBA	45 / 42 / 40	49 / 45 / 41	49 / 45 / 41
Sound Power (Cooling)		dBA	61	65	65

Outdoor Units			ARXM71R	AZAS100MV1	AZAS100MY1
Dimensions	Height x Width x Depth	mm	734 x 954 x 401	990 x 940 x 320	990 x 940 x 320
Weight		kg	49	70	70
Electrical Details	Power Supply		1ph	1ph	3ph
	Maximum Input Current (MCA)	A	14.93	21.2	13.9
	Max Fuse Size	A	16	25	16
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)
Pipework	Maximum Length	m	30	30	30
	Maximum Vertical Rise	m	20	30	30
	Precharged to	m	10	30	30
	Additional charge	g/m	0.35	N/A	N/A
	Holding charge	kg	1.15	2.60	2.60
Sound Pressure (Cooling)	Nom / Night Quiet	dBA	52	53 / 44	53 / 44
Sound Pressure (Heating)	Nom / Night Quiet	dBA	52	57 / 44	57 / 44
Sound Power (Cooling)		dBA	65	70	70
Operating Range (Cooling)	Min / Max	°CDB	-10/46	-5 / 46	-5 / 46
Operating Range (Heating)	Min / Max	°CWB	-15/18	-15 / 15.5	-15 / 15.5
Air Flow Rate (Cooling)	Nominal	m³/sec	0.776	1.150	1.150

## Accessories:

Accessory Ref	Description
BRP069C81	Wifi adaptor for connection to on-line controller
BRC1H52W	Wired touch screen remote controller - White (Included as standard)
BRC1H52S	Wired touch screen remote controller - Silver
BRC1H52K	Wired touch screen remote controller - Black
BRC7EA631	Wireless remote controller for class 71
BRC7EA632	Wireless remote controller for class 100
K.CGL	Condensing unit guard (1450 x 1150 x 650)
K.CGM	Condensing unit guard (1150 x 1150 x 650)
K.CWB140-2	Wall bracket (140kg, 540mm support arm)
K.CWB90-2	Wall bracket (90kg, 500mm support arm)
K.DT1	Condensate drip tray for use with K.CWB90-2

Accessory Ref	Description
K.DT2	Condensate drip tray for use with K.CWB140-2
K.RSS	Wireless room mounted temperature sensor and receiver
KLIC-DI	KNX Interface for Sky Air and VRV systems
KRCS01-4	Remote room mounted temperature sensor
KRP4A53 and UK.FB2	Unit/group adaptor PCB for remote on/off, status indication and temperature setting
RS-SE	Service and configuration tool for K.RSS
RTD-10 and UK.FB2	Enhanced function PCB for Sky Air and VRV. Duty rotation, Lead Lag control and heating interlock
RTD-20 and UK.FB2	Energy control PCB for Sky Air and VRV
RTD-NET and UK.FB2	Modbus interface PCB for Sky Air and VRV

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)