



## FTXA-D / RXA-A/B (8) stylish



# Seiren Stylish

## Where innovation meets creativity

Utilising the latest textured printing technology, Stylish is now available in five extra colours to blend effortlessly into any interior. Advanced airflow technology and an intelligent thermal sensor ensure a perfectly balanced climate throughout the room, while near-silent operation keeps your space calm and undisturbed. And with Daikin's Flash Streamer technology, the air you breathe stays fresh, clean, and allergen-free — so you can relax, focus, or entertain in total comfort.

### Refined design, effortlessly elegant

Applying the latest UV printing technologies, Seiren Stylish comes in five textured finishes designed to mimic woods, fabrics and leather. Blend your unit seamlessly into any décor - whether in a sophisticated home or a high-end boutique. The combination of sleek form with smart function makes Seiren the perfect comfort system for your space.

### Subtle airflow, complete comfort

Thanks to the Coanda effect, airflow is gently guided along ceilings or walls, creating a soft, natural climate throughout the room. This ensures even temperature distribution, eliminating drafts and creating a space that feels consistently pleasant — whether you're hosting friends, unwinding at home, or welcoming customers into a serene setting.

### Comfort that senses your needs

An intelligent thermal sensor reads the room's surface temperatures and intuitively adjusts the airflow to match. It begins by evenly spreading air throughout the space, then shifts to target specific zones that need heating or cooling. The result? A perfectly balanced environment that feels tailored to your daily rhythms — without you lifting a finger.

### Breathe well, live well

Daikin's Flash Streamer technology purifies your air continuously, breaking down allergens and odours at a molecular level. Whether it's pollen, pet dander, or lingering smells, the result is a fresher, cleaner space where you can breathe freely — ideal for homes focused on wellness and shops that care about customer comfort.

### Daikin Onecta App

Control your air conditioning with your phone through Daikin's own Onecta App. Available on Apple and Android, control your system with ease, from anywhere. Enjoy easy voice control of your units by connecting Onecta to Google Home or Amazon Alexa.

### Quiet by design

This unit is practically silent in operation — quieter than a soft whisper. It maintains the ideal indoor climate without interrupting your sleep, your thoughts, or your conversations, making it perfect for bedrooms, reading corners, and tranquil retail spaces alike.



Grey fabric style with black body  
FTXA-DG



Light wood style with white body  
FTXA-DP



Colourful fabric style with white body  
FTXA-DC



Dark brown leather style with black body  
FTXA-DL



Oak wood style with black body  
FTXA-DY



ARC466A85



# FTXA-D / RXA-A/B (8) stylish

**R-32** BLUEEVOLUTION

Seiren Stylish	Grey Fabric Pattern	CTXA15DG	FTXA20DG	FTXA25DG	FTXA35DG	FTXA42DG	FTXA50DG
	Colourful Fabric Pattern	CTXA15DC	FTXA20DC	FTXA25DC	FTXA35DC	FTXA42DC	FTXA50DC
	Pine Wood Pattern	CTXA15DP	FTXA20DP	FTXA25DP	FTXA35DP	FTXA42DP	FTXA50DP
	Oak Wood Pattern	CTXA15DY	FTXA20DY	FTXA25DY	FTXA35DY	FTXA42DY	FTXA50DY
	Dark Brown Leather Pattern	CTXA15DL	FTXA20DL	FTXA25DL	FTXA35DL	FTXA42DL	FTXA50DL
Capacity	UK Total Cooling	Multi Combination Only	1.95	2.44	3.32	4.11	4.89
	UK Sensible Cooling		1.95	1.96	2.43	3.01	3.56
	Nominal Cooling		2.0	2.5	3.4	4.2	5.0
	Nominal Heating		2.5	2.8	4.0	5.4	5.8
Seasonal Efficiency (EN14825) COOLING	Energy Label		A+++	A+++	A+++	A++	A++
	Pdesign		2.0	2.5	3.4	4.2	5.0
	SEER		8.75	8.74	8.73	7.50	7.33
	Annual Energy Consumption		80	101	136	196	239
Seasonal Efficiency (EN14825) HEATING	Energy Label		A+++	A+++	A+++	A++	A++
	Pdesign		2.40	2.45	2.50	3.80	4.00
	SCOP		5.15	5.15	5.15	4.60	4.60
	Annual Energy Consumption		652	666	680	1150	1217
Air Flow Rate (Cooling)	High / Med / Low / Silent	0.183 / 0.137 / 0.102 / 0.077	0.183 / 0.137 / 0.102 / 0.077	0.192 / 0.143 / 0.102 / 0.077	0.198 / 0.143 / 0.102 / 0.077	0.218 / 0.163 / 0.120 / 0.077	0.225 / 0.173 / 0.127 / 0.087
Dimensions	Height / Width / Depth	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189
Weight		12	12	12	12	12	12
Sound Pressure (Cooling)	High / Med / Low / Silent	39/32/25/21	39/32/25/19	40/33/25/19	41/33/25/19	45/37/29/21	46/39/31/24
Sound Power (Cooling)		57	57	57	60	60	60

Outdoor Units		Multi Combination Only	RXA20A8	RXA25A8	RXA35A8	RXA42B8	RXA50B8
Dimensions	Height x Width x Depth	Multi Combination Only	550 x 840 x 350	550 x 840 x 350	550 x 840 x 350	734 x 870 x 373	734 x 870 x 373
Weight			32	32	32	50	50
Electrical Details	Power Supply		1ph	1ph	1ph	1ph	1ph
	Maximum Input Current (MCA)		9.88	11.17	12.29	12.8	12.8
	Max Fuse Size		10	13	13	16	16
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas		1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)
Pipework	Maximum Length		20	20	20	30	30
	Maximum Vertical Rise		15	15	15	20	20
	Precharged to		10	10	10	10	10
	Additional charge		20	20	20	20	20
	Holding charge		0.76	0.76	0.76	1.1	1.1
Sound Pressure (Cooling)	Nominal	46	46	49	48	48	
Sound Power (Cooling)		59	59	61	62	62	
Operating Range (Cooling)	Min / Max	-10/46	-10/46	-10/46	-10/46	-10/46	
Operating Range (Heating)	Min / Max	-15/18	-15/18	-15/18	-15/18	-15/18	
Air Flow Rate (Cooling)	Nominal	0.567	0.567	0.600	0.777	0.777	

Meets ETL criteria. Accessories: ● ● ● ● ●

Accessory Ref	Description
EKRS21	Wire harness for new S21 port for all marked (*) options
BRC073*	Wired remote control – connection cable required
BRCW901A03	3m extension cord required for wired remote controller BRC073
BRCW901A08	8m extension cord required for wired remote controller BRC073
K.CG.M	Condensing unit guard (1150 x 1150 x 650)
K.CG.S	Condensing unit guard (750 x 1050 x 460)
K.CWB90-2	Wall bracket (90kg, 500mm support arm)
K.DT1	Condensate drip tray for use with K.CWB90-2
K.FF600S	Two flexi-feet (Standard 600mm x 185mm x 100mm) to mount the outdoor unit
KLIC-DDV3*	KNX interface for Split type systems
KRP413A1S*	Adaptor PCB for remote on/off control – constant/pulse contact
KRP928A2S*	Adaptor PCB for interface to Daikin centralised control systems
RTD-RA*	Adaptor PCB for Modbus connection and/or extended system functions



### Notes & Features:

- > All fan coils are supplied with infrared remote controller ARC466A85
- > Fan with Coanda effect for optimum air distribution and indoor comfort
- > Grid eye sensor redirects air away from the occupants in the room
- > Flash Streamer technology helps improve indoor air quality
- > Antibacterial Filter for effectively arresting small particulates

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)